

RHINOFLOOR
PROFESSIONAL 70

| TECHNICAL DATA                                     |                            | STANDARD                                                                                                                     |
|----------------------------------------------------|----------------------------|------------------------------------------------------------------------------------------------------------------------------|
| CLASSIFICATION                                     |                            |                                                                                                                              |
| Classification                                     | EN ISO 10582               | Heterogeneous compact floor covering based on polyvinyl chloride                                                             |
|                                                    | EN ISO 10874               | Commercial: 34<br>Industrial: 43                                                                                             |
| Wear layer binder content                          | EN ISO 10582               | Type 1                                                                                                                       |
| TECHNICAL CHARACTERISTICS                          |                            |                                                                                                                              |
| Total thickness                                    | EN ISO 24346               | 2.0 mm                                                                                                                       |
| Total weight                                       | EN ISO 23997               | 2650 g/m <sup>2</sup>                                                                                                        |
| Wear layer thickness                               | EN ISO 24340               | 0.70 mm                                                                                                                      |
| Surface treatment                                  |                            | Top Clean™                                                                                                                   |
| Form of delivery                                   | EN ISO 24341 Sheet (rolls) | approx. 25 running meters x 200 cm *                                                                                         |
|                                                    | * 2m full rolls to order   | Art. no. 25104 .... 3 digit colour number<br>approx. 25 running meters x 400 cm<br>Art. no. 25103 .... 3 digit colour number |
| PERFORMANCES FOR CE MARKING REQUIREMENTS (EN14041) |                            |                                                                                                                              |
| Declaration of Performance                         | EN 1401                    | 0132-0061-DoP-2016-01                                                                                                        |
| Reaction to fire                                   | EN ISO 13501 - 1           | Bfl-s1 glued over concrete and wood substrates                                                                               |
| Electrostatic properties                           | EN 1851<br>EN 1081         | < 2.0 kV on concrete<br>R1 > 10 <sup>10</sup> Ω                                                                              |
| Thermal resistance                                 | EN ISO 10456               | 0.02 m² K/W                                                                                                                  |
| Slip resistance                                    | EN 13893                   | μ ≥ 0.3                                                                                                                      |
| TECHNICAL PERFORMANCES                             |                            |                                                                                                                              |
| Residual indentation                               | EN ISO 24343-1             | Required value: ≤ 0.10 mm<br>Best measured value*: 0.04mm                                                                    |
| Impact sound reduction                             | NF S31-074                 | Class B                                                                                                                      |
| Slip resistance <sup>(1)</sup>                     | DIN 51130                  | R10                                                                                                                          |
| Furniture leg                                      | EN 424                     | No damage                                                                                                                    |
| Castor chair                                       | ISO 4918                   | No damage                                                                                                                    |
| Curl resistance to heat                            | EN ISO 23999               | ≤ 8mm                                                                                                                        |
| Light fastness                                     | EN ISO 105-B02             | ≥ 6                                                                                                                          |
| Dimensional stability                              | EN ISO 23999               | ≤ 0.10 %                                                                                                                     |
| Chemical resistance                                | EN ISO 26987               | Not affected (0)                                                                                                             |
| Underfloor heating                                 |                            | Suitable                                                                                                                     |
| ENVIRONMENTAL PERFORMANCES                         |                            |                                                                                                                              |
| Total VOC emissions                                | ISO 16000-9                | ≤ 100 µg/m <sup>3</sup> (after 28 days)                                                                                      |

\* for information not binding
(1) please note that slip resistance may be impacted by usage and cleaning operations
According to European Regulation N° 305/2011 for CE Marking

PROVINCIAL FLOORCOVERINGS LTD
Unit 9, Raheen Business Park, Limerick V94 W863
Unit 1 & 2, Oak Close, Western Business Park, Dublin D12 E540
Unit 1 & 2, York Retail Park, 1 York Road, Belfast BT15 3GU
Tel. +353 (0) 61 227100
Tel. +353 (0)1 6263913
Tel. +0044 (0)28 9075 3202
Fax. +353 (0) 61 227000
Fax. +353 (0)1 4604669
Fax. +0044 (0)28 9075 3901
Email. sales@pfl.ie
Email. salesdublin@pfl.ie
Email. salesbelfast@pfl.ie

Visit us at www.pfl.ie @ PFL\_Ireland Provincial-Floorcoverings-Ltd



- > Comfort and trendy design
- > Heterogeneous compact vinyl
- > R10 slip resistance
- > Easy maintenance TopClean™ PUR



Phthalate Free  
100%

Heterogeneous  
Compact Vinyl

 **4m**  
rolls & cuts  
ex-stock  
**2m**  
order only

 No wax  
No polish

**Traffic & Slip  
Resistance**  
**0.70** wearlayer  
**R10** slip resistance



**Fossil Light Grege**  
4m:25103 102 2m:25104 012  
LRV: 41.80



**Fossil Grege**  
4m:25103 014 2m:25104 014  
LRV: 31.57



**Stylish Concrete Grey**  
4m:25103 009 2m:25104 009  
LRV: 35.97



**Stylish Concrete Dark Grey**  
4m: 25103 011 2m: 25104 011  
LRV: 16.38



**Cliff Oak Grey**  
4m:25103 005 2m:254104 005  
Pattern Repeat: 12.50 x 100 cm  
LRV: 32.93



**Cliff Oak Beige**  
4m:25103 004 2m:25104 004  
Pattern Repeat: 12.50 x 100 cm  
LRV: 37.72



**Cliff Oak Brown**  
4m:25103 006 2m:25104 006  
Pattern Repeat: 12.50 x 100 cm  
LRV: 23.53



**Cliff Oak Dark Brown**  
4m: 25103 007 2m:25104 007  
Pattern Repeat: 12.50 x 100 cm  
LRV: 15.15



**Elegant Oak Natural**  
4m:25103 000 2m:25104 000  
Pattern Repeat: 16.66 x 100 cm  
LRV: 33.18



**Elegant Oak Light Brown**  
4m:25103 001 2m: 25104 001  
Pattern Repeat: 16.66 x 100 cm  
LRV: 24.37



**Elegant Oak Brown**  
4m: 25103 002 2m:25104 002  
Pattern Repeat: 16.66 x 100 cm  
LRV: 18.14



**Elegant Oak Dark Brown**  
4m: 25103 003 2m:25104 003  
Pattern Repeat: 16.66 x 100 cm  
LRV: 13.85



- > Comfort and trendy design
- > Heterogeneous compact vinyl
- > R10 slip resistance
- > Easy maintenance TopClean™ PUR
- > Commercial: 34 Industrial: 43

